

# PRODUCT DATASHEET

## DST COMP 11 W/865 B22D

OSRAM DULUXSTAR® COMPACT | CFLi, stick shape, with screw base



## TECHNICAL DATA

### Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	220...240 V
Nominal current	110 mA
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor $\lambda$	$\geq 0.50$

### Photometrical data

Luminous flux	570 lm
Luminous efficacy	52 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865

### Light technical data

Warm-up time (60 %)	60.00 s
Starting time	$\leq 2.0$ s

### Dimensions & Weight

Overall length	122.00 mm
Diameter	41.00 mm
Maximum diameter	41 mm
Product weight	59.00 g

### Lifespan

Number of switching cycles	4000
----------------------------	------

### Additional product data

Base (standard designation)	B22d
Mercury content	2.0 mg
Mercury-free	No

### Capabilities

Dimmable	No
----------	----

### Country-specific categorizations

ILCOS	FBT-11/65/1B-220/240-B22D
Order reference	DSTAR 11W/865 2

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	120.00 mm
Height	41.00 mm
Width	41.00 mm

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321112859	Folding box 1	44 mm x 44 mm x 123 mm	104.00 g	0.24 dm <sup>3</sup>
4008321874948	Shipping box 20	218 mm x 176 mm x 142 mm	1480.00 g	5.45 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.