

PRODUCT DATASHEET

DULUX D/E 10 W/3000 K G24q-1

OSRAM DULUX® D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product benefits

- Extremely economical
- Good quality of light

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base



TECHNICAL DATA

Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W

Photometrical data

Light color (designation)	LUMILUX Warm White
Color temperature	3000 K
Light color	30

Dimensions & Weight

Overall length	103.00 mm
Diameter	12.00 mm
Product weight	43.2 g

Additional product data

Base (standard designation)	G24q-1
Mercury content	3.0 mg

Country-specific categorizations

Order reference	DULUX D/E 10W/8
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24q-1
Length	103.00 mm
Height	12.00 mm
Width	12.00 mm

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830197	Folding box 1	35 mm x 35 mm x 118 mm	50.20 g	0.14 dm ³
4008321830203	Shipping box 10	186 mm x 81 mm x 132 mm	556.00 g	1.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.