

# PRODUCT DATASHEET DULUX D/E 13 W/3000 K G24q-1

OSRAM DULUX® D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



#### Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

#### Product benefits

- Extremly economical
- Good quality of light

#### **Product features**

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base



## **TECHNICAL DATA**

## Electrical data

Nominal wattage	13 W
Construction wattage	13.00 W

#### Photometrical data

Light color (designation)  LUMILUX Cool White	
Color temperature	3000 K
Light color	30

# Dimensions & Weight

Overall length	131.00 mm
Diameter	12.00 mm
Product weight	57.7 g

# Additional product data

Base (standard designation)	G24q-1
Mercury content	3.0 mg

# Country-specific categorizations

Order reference	DULUX D/E 13W/8

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24q-1
Length	131.00 mm
Height	12.00 mm
Width	12.00 mm

# **EQUIPMENT / ACCESSORIES**

- Suitable for operation on electronic control gear

# Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830333	Folding box	35 mm x 35 mm x 145 mm	65.70 g	0.18 dm <sup>3</sup>
4008321830340	Shipping box 10	187 mm x 81 mm x 163 mm	720.00 g	2.47 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.