

PRODUCT DATASHEET CFL SQUARE 16 W/827 GR10Q

OSRAM CFL SQUARE® 4 pins | Square CFLni with 4-pin GR10q base for ECG/CCG operation



Areas of application

- Low-profile wall and ceiling luminaires
- Public buildings, reception areas, offices, corridors, etc.
- Shops
- Supermarkets and department stores
- Hotels, restaurants

Product benefits

- Square shape provides uniform distribution of light
- No shadows at either end and no dark patches
- Extremely low profile

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in GR10q base
- Good color rendering index






TECHNICAL DATA

Electrical data

Nominal wattage	16 W
Construction wattage	16.70 W
Nominal voltage	103 V
Nominal current	0.2 A

Photometrical data

Luminous flux	1050 lm
Luminous efficacy	63 lm/W
Light color (designation)	LUMILUX INTERNA
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.88
Rated LLMF at 6,000 h	0.85
Rated LLMF at 8,000 h	0.82
Rated LLMF at 12,000 h	0.78



Dimensions & Weight

Overall length	136.00 mm
Diameter	13.00 mm
Product weight	64.4 g

Temperatures & operating conditions

Ambient temperature range	-5+40 °C
---------------------------	----------

Lifespan

Service life	7500 h ¹⁾
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.88
Rated lamp survival factor at 12,000 h	0.59
Lifespan B50	10000 h

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	GR10q
Mercury content	3.0 mg
Design / version	OSRAM CFL SQUARE® 4-Pin

Capabilities

able	Yes
------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	17.00 kWh/1000h

Country-specific categorizations

ILCOS	FSS-16/827-E-GR10q
Order reference	CFL SQUARE 16W/

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	CFLNI
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GR10q
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE

Claim of equivalent power	No
Length	136.00 mm ¹⁾
Height	27.5 mm
Width	141 mm
Chromaticity coordinate x	0,463
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546534
Model number	AC34308

¹⁾ Maximum

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

	Documents and certificates	Document name
POF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4073688-EN-01 - CFL SQUARE
POF	Certificates	EAC RU C-DE.HA46.B.01131_21 21.05.2021-20.05.2026 Expert Certification - CFLpin
POF	Certificates	EAC N RU D-DE.MU62.B.00933_20 06.03.2020-05.03.2025 Prommash Test - CFLpin

Photometric and lighting design files	Document name
Spectral power distribution	349636_FL_827

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300816890	Folding box 1	29 mm x 152 mm x 152 mm	118.00 g	0.67 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300816906	Shipping box 20	326 mm x 322 mm x 185 mm	2834.00 g	19.42 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.