

## PRODUCT DATASHEET

### CFL SQUARE 28 W/835 GR10Q

OSRAM CFL SQUARE® 4 pins | Square CFLni with 4-pin GR10q base for ECG/CCG operation



#### Areas of application

- Low-profile wall and ceiling luminaires
- Public buildings, reception areas, offices, corridors, etc.
- Shops
- Supermarkets and department stores
- Hotels, restaurants

#### Product benefits

- Square shape provides uniform distribution of light
- No shadows at either end and no dark patches
- Extremely low profile

#### Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in GR10q base
- Good color rendering index




TECHNICAL DATA

Electrical data

Nominal wattage	28 W
Construction wattage	29.10 W
Nominal voltage	108 V
Nominal current	0.32 A

Photometrical data

Luminous flux	1900 lm
Luminous efficacy	65 lm/W
Light color (designation)	LUMILUX White
Color temperature	3500 K
Color rendering index Ra	≥80
Light color	835
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.88
Rated LLMF at 6,000 h	0.85
Rated LLMF at 8,000 h	0.82
Rated LLMF at 12,000 h	0.78



349644\_FL\_835

Dimensions & Weight

Overall length	204.00 mm
Diameter	18.20 mm
Product weight	128.00 g

Temperatures & operating conditions

Ambient temperature range	-5...+40 °C
---------------------------	-------------

## Lifespan

Service life	7500 h <sup>1)</sup>
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.88
Rated lamp survival factor at 12,000 h	0.59
Lifespan B50	10000 h

1) With preheat ECG

## Additional product data

Base (standard designation)	GR10q
Mercury content	3.0 mg
Design / version	OSRAM CFL SQUARE® 4-Pin

## Capabilities

Dimmable	Yes
----------	-----

## Certificates & Standards

Energy efficiency class	G
Energy consumption	30.00 kWh/1000h

## Country-specific categorizations

ILCOS	FSS-28/835-E-GR10q
Order reference	CFL SQUARE 28W/

## Energy labelling regulation data acc EU 2019/2015

Lighting technology used	CFLNI
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GR10q
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE

Claim of equivalent power	No
Length	204.00 mm <sup>1)</sup>
Height	33.0 mm
Width	207 mm
Chromaticity coordinate x	0,409
Chromaticity coordinate y	0,394
Beam angle correspondence	SPHERE_360
EPREL ID	546539
Model number	AC34313

1) Maximum




### EQUIPMENT / ACCESSORIES


– Suitable for operation on electronic and conventional control gear

### Safety advice

– In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

### DOWNLOAD DATA

Documents and certificates	Document name
 Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4073688-EN-01 - CFL SQUARE
 Certificates	EAC RU C-DE.HA46.B.01131_21 21.05.2021-20.05.2026 Expert Certification - CFLpin
 Certificates	EAC N RU D-DE.MU62.B.00933_20 06.03.2020-05.03.2025 Prommash Test - CFLpin

Photometric and lighting design files	Document name
 Spectral power distribution	349644_FL_835

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300816982	Folding box 1	220 mm x 35 mm x 220 mm	251.00 g	1.69 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300816999	Shipping box 20	457 mm x 389 mm x 251 mm	5772.00 g	44.62 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.