

# PRODUCT DATASHEET HQI-T 70 W/WDL

POWERSTAR HQI®-T G12 | Metal halide lamps with quartz technology for enclosed luminaires



#### Areas of application

- Shopping arcades
- Exhibition halls and trade fairs
- Factories and workshops
- Pedestrian zones, public squares
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

## **Product benefits**

- High efficiency
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

## Product features

- POWERSTAR® quartz technology
- Light colors: warm white (WDL), neutral white (NDL)





# TECHNICAL DATA


# Electrical data

Nominal wattage	70 W
Construction wattage	75.00 W
Nominal voltage	101 V
Ignition voltage	3.6/5.0 kVp <sup>1)</sup>
Operating mode Conventional control gear (CCG) and ignitor, Electronic cont (ECG)	
Nominal current	0.95 A
PFC capacitor at 50 Hz	12 μF

<sup>1)</sup> Minimum / Maximum

## Photometrical data

Luminous flux	5400 lm
Luminous efficacy	72 lm/W
Color temperature	3075 K
Color rendering index Ra	73
Light color	730
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.80
Rated LLMF at 6,000 h	0.75
Rated LLMF at 8,000 h	0.70
UV protection	Yes



384079\_HQI\_T\_WDL\_G12

# Dimensions & Weight

Overall length	84.00 mm
----------------	----------

Light center length (LCL)	56,0 mm		
Diameter	25,0 mm		
Product weight	30.00 g		
Temperatures & operating conditions			
Maximum permitted pinch temperature	280 °C		
Lifespan			
Rated lamp survival factor at 2,000 h	0.87		
Rated lamp survival factor at 4,000 h	0.85		
Rated lamp survival factor at 6,000 h	0.75		
Rated lamp survival factor at 8,000 h	0.60		
Lifespan B50	9000 h		
Additional product data			
Base (standard designation)	G12		
Mercury content	13.0 mg		
Design / version	Clear		
Capabilities			
Dimmable	No		
Burning position	Any		
Enclosed luminaire required	Yes		
Hot restart	No		
Certificates & Standards			
Energy efficiency class	G		
Energy consumption	76.00 kWh/1000h		
Country-specific categorizations			
ILCOS	MT/UB-70/730-H/E/SL-G12-25/84		
Order reference	HQI-T 70W/WDL U		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	MH		
Non-directional or directional	NDLS		
Mains or non-mains	NMLS		

Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	84.00 mm
Height	25,0 mm
Width	25,0 mm
Beam angle correspondence	SPHERE_360
EPREL ID	666225
Model number	AM42352

# Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

## ADDITIONAL PRODUCT INFORMATION

- Burning position: In horizontal burning position of lamp, base pins must be positioned in such a way that they form a horizontal plane.

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	High Intensity Discharge Lamp UI	
PDF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4072118-EN-12 - HQI	
PDF	Certificates	EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped	
PDF	Certificates	EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH	
	Photometric and lighting design	files Document name	

Photometric and lighting design files	Document name
Spectral power distribution	384079_HQI_T_WDL_G12

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321974341	Folding box 1	42 mm x 42 mm x 111 mm	40.00 g	0.20 dm <sup>3</sup>
4008321974358	Shipping box 12	180 mm x 140 mm x 127 mm	567.00 g	3.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.