

# PRODUCT DATASHEET NAV-E 150 W E40

VIALOX® NAV®-E | High-pressure sodium vapor lamps for open and enclosed luminaires



#### Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

#### Product benefits

- High luminous efficacy

#### **Product features**

- Service lifetime: 3 years (at approx. 11 h/day)



## TECHNICAL DATA

## Electrical data

Nominal wattage	150 W
Construction wattage	150.00 W
Nominal voltage	100 V
Ignition voltage	3.3/5.0 kVp <sup>1)</sup>
Operating mode	Conventional control gear (CCG) and ignitor
Nominal current	1.8 A

<sup>1)</sup> Minimum / Maximum

## Photometrical data

Luminous flux	14500 lm
Luminous efficacy	97 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.97
Rated LLMF at 4,000 h	0.96
Rated LLMF at 6,000 h	0.95
Rated LLMF at 8,000 h	0.94
Rated LLMF at 12,000 h	0.92
Rated LLMF at 16,000 h	0.91
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (standard co.)	97 lm/W
UV protection	No

# Dimensions & Weight

Overall length	226.00 mm
Diameter	91 mm
Product weight	200.00 g

# Temperatures & operating conditions

Maximum permitted outer bulb temperature	310 °C
Maximum permitted base edge temperature	210 °C

# Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.96
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.85
Lifespan B10	16000 h
Lifespan B5	12000 h
Lifespan B50	28000 h
Operation mode LLMF/LSF	50 Hz

# Additional product data

Base (standard designation)	E40
Mercury content	19.9 mg
Mercury-free	No
Design / version	Coated
Product remark	Phased out in the EU as non ErP compliant according to EU directive 245/2009

# Capabilities

Dimmable	Yes 1)
Burning position	Any
Enclosed luminaire required	No

<sup>1)</sup> In combination with POWERTRONIC PTo

### Certificates & Standards

Energy efficiency class	A+
Energy consumption	165.00 kWh/1000h

## Country-specific categorizations

ILCOS	SE-150-H/E/SL-E40-91/226
Order reference	NAV-E 150W E40

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E40
Length	226.00 mm

Height	91 mm
Width	91 mm

## Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Protect from spray water.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	High-Intensity-Discharge lamps. Operation instructions

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300015613	Round wrap 1	235 mm x 95 mm x 95 mm	203.75 g	2.12 dm <sup>3</sup>
4050300219837	Shipping box 12	427 mm x 255 mm x 334 mm	3086.17 g	36.37 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.