

PRODUCT DATASHEET NAV-T 250 W E40

VIALOX® NAV®-T | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- High luminous efficacy

Product features

- Service lifetime: 3 years (at approx. 11 h/day)



TECHNICAL DATA

Electrical data

Nominal wattage	250 W
Nominal voltage	100 V
Ignition voltage	3.3/5.0 kVp ¹⁾
Nominal current	3 A

¹⁾ Minimum / Maximum

Photometrical data

Luminous flux	28000 lm
Luminous efficacy	112 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.97
Rated LLMF at 4,000 h	0.96
Rated LLMF at 6,000 h	0.95
Rated LLMF at 8,000 h	0.94
Rated LLMF at 12,000 h	0.92
Rated LLMF at 16,000 h	0.91
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (standard co.)	112 lm/W
UV protection	No

Dimensions & Weight

Overall length	257.00 mm
Length	257.00 mm
Light center length (LCL)	158,0 mm
Diameter	47 mm
Product weight	173.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	400 °C
Maximum permitted base edge temperature	250 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.98
Rated lamp survival factor at 8,000 h	0.96
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.85
Lifespan B10	16000 h
Lifespan B5	12000 h
Lifespan B50	28000 h
Operation mode LLMF/LSF	50 Hz

Additional product data

Base (standard designation)	E40
Mercury content	19.9 mg
Mercury-free	No
Design / version	Clear
Product remark	Phased out in the EU as non ErP compliant according to EU directive 245/2009

Capabilities

Dimmable	Yes 1)
Burning position	Any
Enclosed luminaire required	No

¹⁾ In combination with POWERTRONIC PTo

Certificates & Standards

Energy efficiency class	A+
Energy consumption	275.00 kWh/1000h

Country-specific categorizations

ILCOS	ST-250-H/E/SL-E40-47/257
Order reference	NAV-T 250W E40

Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	High-Intensity-Discharge lamps. Operation instructions

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300015675	Sleeve 1	325 mm x 51 mm x 56 mm	202.00 g	0.93 dm ³
4050300214009	Shipping box 12	270 mm x 350 mm x 225 mm	2815.00 g	21.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.