

PRODUCT DATASHEET HO 54 W/940

LUMILUX® DE LUXE T5 HO | Tubular fluorescent lamps 16 mm, high output, with G5 base



Areas of application

- Industry
- Shops
- Supermarkets and department stores
- Ideal where color rendering is an important factor

Product benefits

- Perfect color matching

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Very good color rendering index
- Dimmable






TECHNICAL DATA

Electrical data

Nominal wattage	54 W
Construction wattage	53.80 W
Nominal voltage	120 V
Nominal current	0.46 A

Photometrical data

Luminous flux	4250 lm
Luminous efficacy	79 lm/W
Luminous flux at 35 °C	4250 lm
Light color (designation)	LUMILUX DE LUXE Cool White
Color temperature	4000 K
Color rendering index Ra	≥90
Light color	940
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.93
Rated LLMF at 6,000 h	0.92
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89



Dimensions & Weight

Overall length	1163.20 mm
Length with base excl. base pins/connection	1149 mm
Diameter	16,0 mm

Tube diameter	16 mm
Product weight	88.02 g
_ifespan	
Service life	19000 h ¹⁾
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.97
Rated lamp survival factor at 20,000 h	0.85
Lifespan B50	24000 h
1) With preheat ECG Additional product data	
Base (standard designation)	G5
Mercury content	2.0 mg
Product remark	Suitable for ECG operation only / Lamp designed for internal luminaire temperatures of 3040 °C; optimum luminous flux achieved at 35 °C
Capabilities	
Dimmable	Yes
Certificates & Standards	
Energy efficiency class	G
Energy consumption	54.00 kWh/1000h
Country-specific categorizations	
ILCOS	FDH-54/940-L/P/-G5-16/1449
Order reference	HO 54W/940
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LFL_T5_HO
Non-directional or directional	NDLS

Light source cap-type (or other electric interface)	G5
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	1163.20 mm
Height	16,0 mm
Width	16,0 mm
Chromaticity coordinate x	0,386
Chromaticity coordinate y	0,374
Beam angle correspondence	SPHERE_360
EPREL ID	546298
Model number	AC34061

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

	Documents and certificates	Document name		
POF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4077892-EN-00 - T5 DE LUXE		
POF	Certificates	EAC RU C-DE HA10.B.00671 16 08 2018 15 0	07 2023 Expert Sertifikaciya FL	
POF	Certificates	EAC N RU D-DE.MU62.B.00801_20 02.03.2020-01.03.2025 Prommash Test - FL		
	Photometric and lighting design files		Document name	
	Spectral power distribution		349616_FL_940	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321233929	Sleeve 1	1,164 mm x 18 mm x 18 mm	123.50 g	0.38 dm ³
4008321233936	Shipping box 10	1,191 mm x 104 mm x 51 mm	1440.00 g	6.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.