

# PRODUCT DATASHEET L 18 W/865

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



#### Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

#### Product benefits

- Proven lamp technology

#### **Product features**

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable






## TECHNICAL DATA

## Electrical data

Nominal wattage	18 W
Construction wattage	19.10 W
Nominal voltage	57 V
Nominal current	0.37 A

## Photometrical data

Luminous flux	1250 lm
Luminous efficacy	65 lm/W
Light color (designation)	LUMILUX Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Rated LLMF at 2,000 h	0.96
Rated LLMF at 4,000 h	0.94
Rated LLMF at 6,000 h	0.93
Rated LLMF at 8,000 h	0.91
Rated LLMF at 12,000 h	0.91
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.96



# Dimensions & Weight

Overall length	604.00 mm
Length with base excl. base pins/connection	590,00 mm
Diameter	25.50 mm
Tube diameter	26 mm

Product weight	77.00 g
ifespan	
Service life	18000 h <sup>1)</sup>
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.99
Rated lamp survival factor at 20,000 h	0.50
Lifespan B50	20000 h
Additional product data  Base (standard designation)	G13
Additional product data	
Base (standard designation)	G13
Mercury content	3.0 mg
Capabilities	
Dimmable	Yes
Certificates & Standards	
Energy efficiency class	G
Energy consumption	20.00 kWh/1000h
Country-specific categorizations	
ILCOS	FD-18/865-E-G13-26/600
Order reference	L 18W/865
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	OTHER_FL
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
	Al-
Connected light source (CLS)	No

Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	604.00 mm
Height	25.50 mm
Width	25.50 mm
Chromaticity coordinate x	0,313
Chromaticity coordinate y	0,337
Beam angle correspondence	SPHERE_360
EPREL ID	546324,546328,1282751
Model number	AC34095,AC34091,AC44077

## Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

#### DOWNLOAD DATA

	Documents and certificates	Document name
POF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4071456-EN-01 - T8
POF	Declarations of conformity	L 18W, 36W, 58W

Photometric and lighting design files	Document name
Spectral power distribution	349641_FL_865

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300517773	Sleeve 1	27 mm x 28 mm x 605 mm	103.00 g	0.46 dm <sup>3</sup>
4050300517780	Shipping box 25	625 mm x 145 mm x 150 mm	2775.00 g	13.59 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.