

PRODUCT DATASHEET CLAS A FR 25 W 230 V E27

CLASSIC A | Incandescent lamps, classic bulb shape



Areas of application

- Domestic applications
- Shops, hotels and restaurants
- Meeting rooms
- Shopping centers
- Luminaires with E27 or B22d holders (screw or bajonet holders)

Product benefits

- Brilliant light (CL clear version)
- Reduced glare and softened shadows (FR frosted version)

Product features

- Non-oxidizing aluminum base

TECHNICAL DATA

Electrical data

Nominal wattage	25 W
Construction wattage	25.00 W
Nominal voltage	230 V
Nominal current	0.11 A

Photometrical data

Luminous flux	220 lm
Luminous efficacy	8 lm/W
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027

Light technical data

Ī	Starting time	0 s
	<u> </u>	

Dimensions & Weight

Overall length	94.00 mm
Diameter	55,0 mm
Product weight	26.75 g

Additional product data

Base (standard designation)	E27	
Mercury content 0.0 mg		
Mercury-free	Yes	
Design / version Frosted		
Product remark	Banned from 1.9.2009 as per EU phase-out plan	

Capabilities

Dimmable

Country-specific categorizations

ILCOS	IAA/F-25-230-E27-60
Order reference	CLAS A FR 25W 2

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	97.00 mm
Height	55,0 mm

h	55,0 mm
---	---------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321419385	Folding box 1	97 mm x 56 mm x 56 mm	35.75 g	0.30 dm ³
4052899349971	Bundle 10			
4008321419392	Bundle 10	112 mm x 97 mm x 285 mm	357.50 g	3.10 dm ³
4008321419408	Shipping box 100	570 mm x 207 mm x 294 mm	3531.00 g	34.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.