

# PRODUCT DATASHEET OTi DALI 35/220...240/700 LT2 L

OPTOTRONIC® Intelligent | - Dimmable DALI SELV LEDset (LT2)



#### Areas of application

- Linear lighting for office, education, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for luminaires of protection class I

#### Product benefits

- Fully programmable via software (DALI Interface)
- Flexible current setting (LEDset2)
- Lifetime: up to 100,000 h (temperature at T  $_{\text{C}}$  = 65 °C, max. 10 % failure rate)
- High-quality dimming of 1...100 % by amplitude dimming (except 80 W versions)
- High quality of light thanks to <1% output ripple current
- Very high efficiency
- $-\,$  Very low standby power consumption: < 0.15 W  $^{\star}$
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

## Versatile scope of application due to OSRAM DALI Technology:

- Easy to use in corridors and restrooms because of three-level Corridor function
- Touch DIM application: easy to control via pushbutton or sensor
- Energy efficient Touch DIM operation due to automatic switch-off at sufficient residual light
- Suitable for emergency Installations (acc. to EN 60598-2-22 and IEC 61347-2-13, appendix J) thanks to DC detection (0 Hz, pulsating DC), on/off switchable
- Feedback of power consumption and operating hours (Fit for SMART GRID)
- Suitable for buildings according to EPBD/BREEAM/LEED due to automatic Constant Lumen Output setting
- Luminaire information for easy maintenance

## Product features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile DALI window driver up to 80 W due to flexible output characteristic
- Supply voltage: 220...240 V
- Available with output current range: up to 2,100 mA
- Constant Lumen Output (CLO)
- Integrated customizable thermal management (Driver Guard)
- DALI-2 certified (Part -101,-102 and -207)

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	35.00 W
Nominal output power	35 W
Nominal voltage	220240 V
Nominal output voltage	2054 V <sup>1)</sup>
Input voltage AC	198264 V <sup>2)</sup>
Input voltage DC	176276 V
U-OUT (working voltage)	60 V
Nominal current	0.18 A
Nominal output current	200700 mA <sup>3)</sup>
Inrush current	32 A
Output current tolerance	±2 % <sup>4)</sup>
Output ripple current (100 Hz)	< 1 %
Mains frequency	50/60 Hz
Total harmonic distortion	< 11 %
Power factor $\lambda$	> 0.95 <sup>5)</sup>
ECG efficiency	≥90 % <sup>6)</sup>
Device power loss	4.4 W <sup>7)</sup>
Max. ECG no. on circuit breaker 10 A (B)	18
Max. ECG no. on circuit breaker 16 A (B)	30
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Power loss in stand-by mode	< 0.5 W

<sup>1)</sup> Maximum 60 V

# Dimensions & Weight



<sup>2)</sup> Permitted voltage range

<sup>3)</sup>  $_{\pm 2\%}$ 

<sup>4)</sup> Within nominal output current range

<sup>5)</sup> Full load at 230 V

<sup>6)</sup> At full load and 230 V

<sup>7) &</sup>lt;sub>Maximum</sub>

Length	360.00 mm
Mounting hole spacing, length	350,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0.51.5 mm <sup>2</sup> 1)
Cable cross-section, output side	0.51.5 mm <sup>2</sup> 1)
Wire preparation length, input side	8.59.5 mm
Wire preparation length, output side	8.59.5 mm
Product weight	275.00 g

<sup>1)</sup> Solid or flexible leads

## Colors & materials

Product color	White
Casing material	Metal
Body material	Metal

# Temperatures & operating conditions

Ambient temperature range	-25+60 °C	
Maximum temperature at tc test point	75 °C	
Max.housing temperature in case of fault	110 °C	
Permitted rel. humidity during operation	585 % <sup>1)</sup>	

<sup>1)</sup> Maximum 56 days/year at 85 %

## Lifespan

ECG lifetime 50000 h / 100000 h <sup>1)</sup>	ECG lifetime	50000 h / 100000 h <sup>1)</sup>
---	--------------	----------------------------------

<sup>1)</sup> At maximum  $T_c = 75^{\circ}\text{C} / 10\%$  failure rate / At  $T_c = 65^{\circ}\text{C} / 10^{\circ}$  failure rate

# Additional product data

Dimmable	Yes
Capabilities	
Encapsulated	No

	Dimmable	Yes	
Dimming interface		DALI / Touch DIM / Touch DIM Sensor	
	Dimming range	1100 % 1)	
	Overheating protection	Automatic reversible	
	Overload protection	Automatic reversible	
	No-load proof	Yes	

Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	I
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

<sup>1)</sup> For maximum nominal output current

## Certificates & Standards

Approval marks – approval	ENEC 10 / VDE / EMC / EL / CE	
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384	
Protection class	I	
Type of protection	IP20	

## LOGISTICAL DATA

Temperature range at storage	-2575 °C
------------------------------	----------

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	conformity EU Declaration of Conformity 3366462	
PDF	Certificates	VDE ENEC Certificate 40038447	
PDF	Certificates	VDE EMC Certificate 40038827	
PDF	EU Data Act	Connected Products and Related Software and Services	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899245389	Unpacked 1		275.00 g	
4052899245396	Shipping box 20	385 mm x 160 mm x 100 mm	5671.00 g	6.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.