

# PRODUCT DATASHEET DR-SUP -60/220-240/24

LED DRIVER SUPERIOR | Constant voltage longlife LED driver



#### Areas of application

- Cove lighting, even in tight spaces
- Wallwasher effect lighting in living rooms, dining rooms, bedrooms, entrances
- Offices, shopping centers, hospitals, restaurants, hotels
- For indoor SELV installations

### Product benefits

- Perfectly matched to 24 V LED flexible strips
- Long reliable life at maximum permitted temperatures
- 5 years guarantee
- Maintenance-free operation and minimal installation costs
- Quick and simple installation
- High efficiency and reliability

### **Product features**

- Available in 30 W, 60 W, 100 W and 200 W
- Integrated cable clamp for independent installation
- Lifetime: up to 60,000 h (at max. tc temperature)
- Type of protection: IP20
- Low ripple current < 5%
- Supply voltage: 220...240 V
- Operating frequency: 50/60 Hz
- Operated with less than 60 V: Safety extra-low voltage (SELV)
- Reversible overtemperature, overload, short-circuit and open-circuit protection


## **TECHNICAL DATA**

## Electrical data

Nominal wattage	60.00 W
Nominal output power	60 W <sup>1)</sup>
Nominal voltage	220240 V
Nominal output voltage	24 V <sup>2)</sup>
Input voltage AC	198264 V <sup>3)</sup>
U-OUT (working voltage)	25 V
Type of current	DC
Nominal current	310 mA
Nominal output current	2500 mA
Inrush current	34 A
Output ripple current (100 Hz)	1.5 %
Mains frequency	5060 Hz
Total harmonic distortion	< 10 % <sup>4)</sup>
Power factor $\lambda$	0.95 4)
ECG efficiency	85 % <sup>5)</sup>
Device power loss	9 W <sup>6)</sup>
Max. ECG no. on circuit breaker 10 A (B)	14
Max. ECG no. on circuit breaker 16 A (B)	22
Max. ECG no. on circuit breaker 25 A (B)	34
Surge capability (L-N)	1 kV
Galvanic isolation	SELV

<sup>1)</sup> From 1 to 60 W

# Dimensions & Weight



<sup>2) &</sup>lt;sub>Maximum 24 V</sub>

<sup>3)</sup> Permitted voltage range

<sup>4)</sup> At full load

<sup>5)</sup> At full load and 230  $\mbox{\rm V}$ 

<sup>6)</sup> At maximum LED load of 60 W

Length	198.00 mm
Mounting hole spacing, length	141 mm
Width	43.00 mm
Height	30.00 mm
Cable cross-section, input side	0.51.5 mm <sup>2</sup>
Cable cross-section, output side	0.51.5 mm <sup>2</sup>
Prewired	No
Wire preparation length, input side	8,0 mm
Wire preparation length, output side	8,0 mm
Product weight	192.00 g

## Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

# Temperatures & operating conditions

Ambient temperature range	-20+55 °C
Maximum temperature at to test point	90 °C
Max.housing temperature in case of fault	110 °C
Temperature range in operation	-20+55 °C
Permitted rel. humidity during operation	585 %

## Lifespan

ECG lifetime	60000 h <sup>1)</sup>

<sup>1)</sup> At maximum  $T_c = 80^{\circ}\text{C} / 10\%$  failure rate

## Additional product data

Encapsulated	No

# Capabilities

Dimmable	No
Dimming interface	Not dimmable
Overheating protection	Yes
Overload protection	Yes
Short-circuit protection	Yes
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	II .

Suitable for emergency lighting	No
Type of connection, output side	Fixed connection (terminal)

## Certificates & Standards

Approval marks – approval	CE / CB / ENEC	
Standards	Acc. To IEC/EN61347-1 / Acc. to IEC 61347-2-13 / Acc. to GB 19510.1 / Acc. to GB 19510.14 / Acc. to EN 55015 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / Acc. to IEC 61000-4-2, 3, 4, 5, 6, 8, 11 / Acc. to IEC 61547 / Acc. to IEC 62384	
Protection class	II	
Type of protection	IP20	

### LOGISTICAL DATA

Temperature range at storage	-40+85 °C
------------------------------	-----------

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DR-SUP 220-240 24
PDF	Declarations of conformity	DR SUP LL

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075437807	Folding box	200 mm x 44 mm x 34 mm	210.00 g	0.30 dm <sup>3</sup>
4058075437814	Shipping box 10	215 mm x 182 mm x 110 mm	2230.00 g	4.30 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.