

PRODUCT DATASHEET

LVED PRO LVED PRO 100/22

LED Pro Outdoor CC Driver | Constant current ECG for LED modules



Areas of application

- Outdoor applications
- Street and urban lighting
- Sports halls

Product benefits

- Safety requirement due to overload, overtemperature, short-circuit protection
- Long lifetime
- High surge protection: up to 6 kV

Product features

- Lifetime up to 50,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	100.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	0.95

Dimensions & Weight

Length	202.00 mm
Width	54.00 mm
Height	32.00 mm
Product weight	566.00 g

Temperatures & operating conditions

Ambient temperature range	-40...+50 °C
Maximum temperature at tc test point	85 °C
Max.housing temperature in case of fault	110 °C
Temperature range in operation	-40...+50 °C

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Protection class	1
------------------	---

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075353220	Folding box 1	227 mm x 82 mm x 49 mm	605.00 g	0.91 dm ³
4058075353237	Shipping box 20	434 mm x 262 mm x 226 mm	12616.00 g	25.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.