

# PRODUCT DATASHEET QTi 1X28/54 DIM

QUICKTRONIC® INTELLIGENT DIM T5 | ECG dimmable 1...10 V for FL 16 mm



#### Areas of application

- Suitable for emergency installations
- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Suitable for luminaires of protection class I

#### **Product benefits**

- Same luminous flux with direct and alternating current
- Perfect lamp start for applications with motion sensors
- Dimming of amalgam lamps without flickering or reduced lifespan
- Very high efficiency thanks to cut-off technology
- Automatic restart after lamp replacement
- ECGs comply with MINERGIE standard due to very low standby consumption
- Configurable emergency power characteristics

#### **Product features**

- Control via 1...10 V interface
- Supply voltage: 220...240 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz

- Line voltage: 198...264 V
- Dimming range: 1...100 % luminous flux
- Lamp start: within 0.6 s
- Lifetime: > 100,000 h (for T = 65  $^{\circ}C$  at T  $_{C}\!)$
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Energy Efficiency Index EEI: A1 BAT
- Overtemperature protection: Thermal management at high  $t_{\rm c}$  temperatures
- Safety: to EN 61347-2-3
- Lamp operation: to EN 60929
- RI suppression: to EN 55015:2006+A1:2007+A2:2009/CISPR 15
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547

# TECHNICAL DATA

#### Electrical data

Nominal wattage	59.00 W
Nominal voltage	220240 V
Input voltage AC	198264 V
Input voltage DC	154276 V
Type of current	AC/DC
Inrush current	24 A
Mains frequency	5060 Hz
Max. ECG no. on circuit breaker 10 A (B)	17 1)
Max. ECG no. on circuit breaker 16 A (B)	28 1)
Operating frequency	44120 kHz

<sup>1)</sup> Type B

# Light technical data

Starting time	0.6 s

# Dimensions & Weight

Length	360.00 mm
Mounting hole spacing, length	350,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0,51,0 mm² / 0.51.5 mm² <sup>1)</sup>
Cable cross-section, output side	0.51.5 mm² / 0,51,0 mm² <sup>1)</sup>
Wire preparation length, input side	8.09.0 mm <sup>2)</sup>
Wire preparation length, output side	8.09.0 mm <sup>2)</sup>
Product weight	273.00 g

<sup>1)</sup> Solid leads / Flexible

#### Colors & materials

Casing material	Metal
Body material	Metal

# Temperatures & operating conditions

<sup>2)</sup> Combi wiring

Ambient temperature range	+10+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

#### Lifespan

<sup>1)</sup> At  $T_{case} = 65$  °C at  $T_{c}$  point / 10 % failure rate

# Capabilities

Dimmable	Yes
Dimming interface	110 V
Dimming range	1100 % <sup>1)</sup>
Overheating protection	Power reduction and switch off at T > 75 °C at the tc point
Overload protection	Automatic switch off, reversible
Max. cable length to lamp/LED module	1.0 m / 1.5 m
Suitable for fixtures with prot. class	I I
Suitable for emergency lighting	Yes
End of lamp life safety shutdown	EOL T.2

<sup>1)</sup> Luminous flux

#### Certificates & Standards

Approval marks – approval	VDE / VDE-EMC / EL / EAC / RCM / CCC
Standards	Acc. to EN 55015; EN 55022 / Acc. to EN 61547 / Acc. to IEC 61000-3-2/EN 61000-3-2
Protection class	1
Type of protection	IP20
Energy efficiency class	A1
EEI – Energy Label	A1 BAT

# LOGISTICAL DATA

Temperature range at storage	-40+85 °C

# DOWNLOAD DATA

	Documents and certificates Document name		
PDF	User instruction / safety instructions	334142_Technical guide - ECGs for T5-lamps	
PDF	User instruction / safety instructions	493509_Technical application guide QUICKTRONIC Intelligent DALI DIM (GB)	
PDF	User instruction / safety instructions	592412_EAC QTi T5 DIM	
PDF	Declarations of conformity	334957_Declaration of conformity	
PDF	Certificates	335135_Manufacturer's declaration – Burning-in of fluorescent lamps	
PDF	Certificates	334953_EMC-Marks approval	
PDF	Certificates	335153_Manufacturer's declaration – Low stand-by	
PDF	Certificates	335169_Manufacturer's declaration – Lamp/ECG combinations: Frequent switching  554891_EAC PT family  335097_INOTEC  335125_ENEC/VDE-Marks approval	
PDF	Certificates		
PDF	Certificates		
PDF	Certificates		
PDF	Certificates	335154_Manufacturer's declaration - EN 55015:2006+A1:2007 (300 MHz)	
PDF	Certificates	504208_VDE-EMC-CERTIFICATE QTI DALI DIM	
	CAD/BIM files	Document name	
PDF	CAD data 3D PDF	313406_360x30x21 1881281	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300870588	Unpacked 1		273.00 g	
4050300870595	Shipping box 20	370 mm x 96 mm x 170 mm	6320.00 g	6.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.