

# PRODUCT DATASHEET PL-CN 111AC-1200-840 40 G1

PrevaLED® COIN 111 AC G1 | LED modules with integrated optics and heat sink



#### Areas of application

- LED replacement for high intensity discharge lamps up to 35 W
- Shop lighting
- Shopping centers
- Exhibition halls
- Museums
- Suitable for indoor applications

#### Product benefits

- Easy and quick design-in for luminaire manufacturers
- Turn-key solution for projects
- 5 year guarantee

#### Product features

- Integrated driver, heat sink and lens optics
- Fits into most existing traditional R111 luminaires
- Available with 24° or 40° beam angle
- Versions with different luminous flux and different color temperatures available
- Lifetime (L70/B50): 35,000 h (temperature at  $T_{\rm C}$  = 68 °C)
- Max. working voltage: 60 V (to be operated only on SELV LED control gear)





## TECHNICAL DATA

## Electrical data

Nominal wattage	15.50 W
Construction wattage	15.50 W
Nominal voltage	230 V
Input voltage range	220240 V
Type of current	AC
Nominal current	75.000 mA
Power factor $\lambda$	≥ 0.90
Flickering metric (Pst LM)	≤1

#### Photometrical data

Total useful luminous flux [PICOS]	1350 lm
Luminous efficacy	87 lm/W
Luminous flux	1200 lm <sup>1)</sup>
Luminous intensity	2600 cd
Nom. useful luminous flux 120° [PICOS]	1300 lm
Flickering metric (Pst LM)	≤1
Color temperature	4100 K
Color rendering index Ra	83
Light color LED	White
Light color (designation)	Neutral White
Standard deviation of color matching	3 sdcm
Rated peak intensity	2600 cd
Lumen main.fact.at end of nom.life time	0.70
Stroboscope effect metric (SVM)	≤0.9

<sup>1) 90 °</sup> 

# Light technical data

Beam angle	40 °
Rated beam angle (half peak value)	40.00 °
Starting time	< 0.5 s

## LED MODULE INFORMATION

Number of LEDs per module	12
---------------------------	----

# Dimensions & Weight



Cable length	500.000
Height	50.00 mm
Diameter	110.7 mm
Product weight	340.00 g

#### Colors & materials

Product color	White

## Temperatures & operating conditions

Ambient temperature range	-4080 °C
Maximum temperature at to test point	80 °C
Temperature range in operation	-4080 °C
Performance temp. acc. to IEC 62717	68 °C

#### Lifespan

Nominal lamp life time	35000 h
Number of switching cycles	> 100000

## Additional product data

Product remark	For current photometric data and important safety, installation and application information, see www.osram.com/led-systems. / All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values / Tolerance for optical and electrical data: +/-10%
----------------	---

## Capabilities

Dimmable	No
----------	----

# Certificates & Standards

Standards	Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 62031 / Acc. to IEC 60598-1 / Acc. to IEC 62471 / CE / ROHS / UL-94
Type of protection	IP20
Energy consumption	16.00 kWh/1000h
Energy efficiency class	F
Energy class of contained light source	F

## Energy labelling regulation data acc EU 2019/2015

Lighting technology used LED
------------------------------

#### DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	EU Declaration of Conformity PL COIN 111 G1 family
PDF	Certificates	664159_ENEC VDE Certificate: PL Cube AC G3
PDF	Certificates	VDE EMC CERTIFICATE 40038324 AC

Photometric and lighting design files	Document name
LDT file (Eulumdat)	540300_PL-CN111AC-G1 1200-840 40

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899165632	Folding box	129 mm x 118 mm x 64 mm	380.00 g	0.97 dm <sup>3</sup>
4052899165649	Shipping box 12	280 mm x 254 mm x 224 mm	5003.00 g	15.93 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# References / Links

- For more information on the multi-level guarantee and the terms and conditions of the guarantee visit www.ledvance.com/system-guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.