

PRODUCT DATASHEET LS AY -PM01/UW/21,5X12/10/1

Medium Profiles for LED Strips | Medium Profiles for LED Strips



Areas of application

- General indoor illumination

Product benefits

- Robust aluminum profile
- Quick and simple installation

TECHNICAL DATA

Dimensions & Weight

Length	1000 mm
Width	21.5 mm
Height	12 mm
Product weight	120.00 g

Colors & materials

Product color	Grey

Temperatures & operating conditions

Ambient temperature range	-15+45 °C
Temperature range in operation	-15+45 °C

Additional product data

Product remark	Can be combined with SUPERIOR UNPROTECTED Strips / Cannot be combined with SUPERIOR PROTECTED Strips / Can be combined with PERFORMANCE UNPROTECTED Strips / Cannot be combined with PERFORMANCE PROTECTED Strips / Can be combined with VALUE UNPROTECTED Strips / Cannot be combined with VALUE
	VALUE UNPROTECTED Strips / Cannot be combined with VALUE
	PROTECTED Strips

LOGISTICAL DATA

Temperature range at storage	-35+85 °C

Accessories Optional

Product image	Product name	EAN
	LS AY -PC/P02/D/1	4058075305762
	LS AY -PM01/MB	4058075276888
	LS AY -PM01/EC/H	4058075277786
	LS AY -PM01/EC	4058075277755

Product image	Product name	EAN
	LS AY -PC/P02/C/1	4058075402225

DOWNLOAD DATA

Documents and certificates		Document name	
PDF	Declarations of conformity	LS AY PM_PF_PW_PC	

Tender texts	Document name
Tender documents	Medium Profiles for LED Strips PM01UW 21 5X12 10 1-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075278318	BAG 1	1,200 mm x 50 mm x 5 mm	121.00 g	0.30 dm ³
4058075278325	Bundle 10	500 mm x 55 mm x 50 mm	1210.00 g	1.38 dm ³
4058075278332	Shipping box 50	1,030 mm x 140 mm x 160 mm	6551.00 g	23.07 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.