

PRODUCT DATASHEET

LS AY -PM05/MB

Medium Profiles for LED Strips | Medium Profiles for LED Strips



Areas of application

- General indoor illumination

Product benefits

- Robust aluminum profile
- Quick and simple installation

TECHNICAL DATA

Dimensions & Weight

| | |
|----------------|---------|
| Length | 14.6 mm |
| Width | 21.4 mm |
| Height | 7.2 mm |
| Product weight | 1.00 g |

Colors & materials

| | |
|---------------|-------------|
| Product color | Transparent |
|---------------|-------------|


Temperatures & operating conditions


| | |
|--------------------------------|--------------|
| Ambient temperature range | -15...+45 °C |
| Temperature range in operation | -15...+45 °C |

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -35...+85 °C |
|------------------------------|--------------|

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|----------------------------|-------------------|
|  | Declarations of conformity | LS AY PM_PF_PW_PC |

| Tender texts | Document name | |
|--|------------------|--|
|  | Tender documents | Medium Profiles for LED Strips PM05MB-EN |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075277007 | Folding box 2 | 80 mm x 120 mm x 5 mm | 3.00 g | 0.05 dm ³ |
| 4058075277014 | Shipping box 100 | 120 mm x 100 mm x 120 mm | 198.00 g | 1.44 dm ³ |
| 4058075277021 | Shipping box 1,000 | 525 mm x 140 mm x 270 mm | 2371.00 g | 19.85 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

