



LEDVANCE

# PRODUCT DATASHEET

## LS AY SUP -CSD/P3

Connectors for TW LED Strips | Connectors for TW LED Strips



SUPERIOR  
CLASS

---

### Areas of application

- General indoor illumination

---

### Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

## TECHNICAL DATA

### Electrical data

Nominal voltage	0...36 V
Nominal current	5000 mA

### Dimensions & Weight

Length	19.6 mm
Width	14.6 mm
Height	7.7 mm
Cable cross-section, input side	0.35...0.75 mm <sup>2</sup>
Product weight	1.8 g

### Colors & materials

Product color	Transparent
---------------	-------------

### Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
Temperature range in operation	-20...+55 °C


### Certificates & Standards


Type of protection	IP00
--------------------	------

## LOGISTICAL DATA

Temperature range at storage	-35...+85 °C
------------------------------	--------------

## DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	LED STRIP ACCESSORIES

Tender texts		Document name
	Tender documents	Connectors for TW LED Strips CSDP3-EN

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451353	BAG 2	80 mm x 120 mm x 5 mm	4.60 g	0.05 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451360	Shipping box 100	120 mm x 100 mm x 120 mm	278.00 g	1.44 dm <sup>3</sup>
4058075451377	Shipping box 1,000	525 mm x 140 mm x 270 mm	3171.00 g	19.85 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.