


# PRODUCT DATASHEET

## LS AY PFM -CSW/P5/50

Connectors for RGBW LED Strips | Connectors for RGBW LED Strips



PERFOR-  
MANCE  
CLASS

### Areas of application

- General indoor illumination

### Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	0...36 V
Nominal current	5000 mA

Dimensions & Weight

Length	24.3 mm
Cable length	50 mm
Width	17.0 mm
Height	7.7 mm
Cable cross-section, input side	0.35...0.75 mm <sup>2</sup>
Product weight	7.6 g

Colors & materials

Product color	Transparent
---------------	-------------

Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
Temperature range in operation	-20...+55 °C


Certificates & Standards


Type of protection	IP00
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-35...+85 °C
------------------------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	LED STRIP ACCESSORIES

Tender texts		Document name
	Tender documents	Connectors for RGBW LED Strips CSWP550-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451148	BAG 2	80 mm x 120 mm x 5 mm	16.20 g	0.05 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451155	Shipping box 100	250 mm x 100 mm x 250 mm	958.00 g	6.25 dm <sup>3</sup>
4058075451162	Shipping box 1,000	520 mm x 520 mm x 270 mm	23642.00 g	73.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.