

PRODUCT DATASHEET

LED PFM DL 6.30 W 3000 K G2S

LED PERFORMANCE DOWNLIGHT G2S | LED downlight luminaires



Areas of application

- Offices
- Shopping malls
- Retail
- Hospitality

Product benefits

- Stylish design
- Die-cast aluminum housing for improved heat dissipation
- Good glare reduction (UGR < 19) and cut off angle up to 30° for comfortable indoor lighting
- Energy savings thanks to high system efficacy: up to 120 lm/W
- External driver design allows for flexible change of control gear
- Low maintenance and operation costs due to long lifetime of LED
- Type of protection: IP54 (room side) provides additional protection against humidity

Product features

- Available with diameter: 4 inch, 6 inch and 8 inch
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- System up with LEDVANCE DRIVER (Driver not included)
- Color rendering index R_a : > 80
- Initial color consistency: < 5 SDCM
- Long lifetime up to 50,000 h



TECHNICAL DATA

Electrical data


Nominal wattage	6.30 W
Nominal voltage	26,5 V
Nominal current	270.000 mA
Power factor λ	> 0.90
Protection class	III
Operating mode	External LED driver

Photometrical data

Luminous flux	817 lm
Luminous efficacy	129 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	< 5 sdcm
Beam angle	65 °
UGR	< 19

Dimensions & Weight

Diameter	112.00 mm
Height	50.00 mm
Product weight	258.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum

Cover material	Polymethylmethacrylate (PMMA)
Mercury content	0.0 mg

Application & Mounting



Ambient temperature range	-20...+45 °C
Temperature range at storage	-20...+70 °C
Type of connection	Cable, 2-pole
Type of protection	IP54/IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	100.0...110.0 mm
Mounting depth	> 30 mm
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LDPFM DL 105 G2S
Photometric and lighting design files		Document name
	IES file (IES)	LDPFM DL 105 830 G2S

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075427501	Folding box 1	174 mm x 74 mm x 177 mm	375.00 g	2.28 dm ³
4058075427518	Shipping box 30	543 mm x 390 mm x 385 mm	12382.00 g	81.53 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.