

PRODUCT DATASHEET SF BLKH S 250 P EM 10W 830 BK IP65

SURFACE BULKHEAD 250 SENSOR EMERGENCY | Robust wall and ceiling luminaire with IP65 protection, high-frequency sensor and integrated emergency lighting function



Areas of application

- Emergency illumination of escape routes
- Antipanic lighting
- Buildings requiring up to 3 h emergency light operation
- Direct replacement for luminaires with fluorescent lamps
- Corridors, stairways, entrance areas
- Passages, underpasses
- Public areas

Product benefits

- Multiple adjustments of sensor range, daylight detection and hold time
- Seamless integration of luminaires with emergency lighting function into general lighting
- Easy wiring thanks to included prewired driver and battery for Emergency lighting function
- Separate covers available for an aesthetic and functional product design
- 3 years guarantee
- Operation of integrated emergency lighting function with long life LiFePO4 battery with 3h battery discharge time
- High luminous efficacy in normal operation
- Suitable for use in dusty and damp locations thanks to high IP rating
- Suitable for use in public areas thanks to high IK rating
- Multiple mounting patterns for convenient installation
- Convenient visualization of results of automatic test with an included control LED
- Simple testing of luminaires with emergency lighting function thanks to integrated automatic test function

Product features

- High frequency sensor for daylight and motion detection
- Certified according to European norms (EN 60598-1:2015; EN 60598-2-22:2014)
- Luminaire suitable for normal lighting and emergency lighting
- Self-contained luminaires
- Emergency lighting function: battery discharge time of 3 h

- Function test of emergency lighting: automatic (AT)
- Battery technology: LiFePO4
- Ambient temperature in operation: 5°...+40 C
- UV-stabilized polycarbonate (PC) housing, PC-diffuser
- Impact resistance: IK10
- Push wire terminal for tool-free connection
- Through-wiring possible


TECHNICAL DATA


Electrical data

Nominal wattage	10.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	350.000 mA
Inrush current	7.47 A
Inrush current time T _{h50}	725 µs
Max. number of luminaires per miniature circuit breaker B16	16
Max. number of luminaires per miniature circuit breaker C10	10
Max. number of luminaires per miniature circuit breaker C16	16
Power factor λ	≥0.5
Total harmonic distortion	< 8 %
Protection class	II .
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	800 lm
Luminous efficacy	80 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Luminous intensity	-
Low flicker	Yes
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °






SF BLKH S 250 P 10W 830 BK IP65 EM

SF BLKH S 250 P 10W 830 BK IP65 EM

Dimensions & Weight

Diameter	250.00 mm
Height	70.00 mm
Product weight	850.00 g



Materials & Colors

Product color	Black
Housing color	Black
RAL Color (most similar)	RAL 9005
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)

Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	+5+40 °C
Type of connection	Screwless terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Outdoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Lifespan L80/B10 at 25 °C	35000 h ¹⁾
Lifespan L80/B50 at 25 °C	35000 h
Lifespan L90/B10 at 25 °C	20000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	350 mA
----------------	--------

Sensor

Type of sensor	Motion / Light
Sensor technology	Microwave
Sensor detection angle	150 °
Sensor controlled switching time	5 s30 min
Detection range of motion sensor	38 m
Detection threshold of daylight sensor	250 lx
Sensor IP rating	IP20

BATTERY

Type of Battery	LiFePO4
Battery size [GMS]	Others
Nominal voltage of battery	3.2 V
Nominal capacity of battery	4500 mAh

Battery charging time	< 24 h
-----------------------	--------

Emergency lighting

Area of emergency application	Anti-panic lighting / Escape route lighting
Type of emergency light operation	Maintained / Non-maintained
Type of emergency operation test	None
Wattage in maintained operation mode	16.5 W
Wattage in emergency operation mode	3,0 W
Luminous flux in maintained operation mode	800 lm
Luminous flux in emergency operation mode	300 lm
Battery life in emergency operation mode	3 h
Integrated test switch	No

Certificates & Standards

Standards	CE / CB
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

EQUIPMENT / ACCESSORIES

- Additional cover rings in different designs available
- Mounting screws and dowels included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	SF BLKH 250, 300 P IP65 EM
PDF	Legal information	LS Insert SF Bulkhead Sensor P
PDF	Legal information	LS Insert SF Bulkhead P EM
PDF	Legal information	Legal insert SF BLKG S P IP65 EM
PDF	Legal information	Informationstext 18 Abs 4 ElektroG

	Documents and certificat	tes	Document name	
PDF	Declarations of conformi	EC declaration SF BLKH S EM LUM		
PDF	Declarations of conformity UKCA		SF BLKH S IP65 EM	
PDF	Declarations of conformity UKCA		SF BLKH S P IP65 EM	
	Photometric and lighting design files		Document name	
	IES file (IES)		SF BLKH 250 10W 3000K S BK IP65 EM	
	IES file (IES)		SF BLKH 250 10W 3000K S BK IP65 EM	
	IES file (IES)		SF BLKH 250 10W 3000K S BK IP65 EM	
	LDT file (Eulumdat)		SF BLKH 250 10W 3000K S BK IP65 EM	
	LDT file (Eulumdat)		SF BLKH 250 10W 3000K S BK IP65 EM	
	LDT file (Eulumdat)		SF BLKH 250 10W 3000K S BK IP65 EM	
	ULD file (DIALux)		SF BLKH S EM BK	
	ROLF file (RELUX)		SF BLKH S EM BK	
	UGR file (UGR table)		SF BLKH S 250 P 10W 830 BK IP65 EM	
	Light distribution curve type cone		SF BLKH S 250 P 10W 830 BK IP65 EM	
	Light distribution curve type polar		SF BLKH S 250 P 10W 830 BK IP65 EM	
	CAD/BIM files		Document name	
	BIM Revit 3D		Surface Bulkhead	
(STP)	CAD STEP 3D		SF BLKH 250	
	Tender texts	Document name		
	Tender documents		250 SENSOR EMERGENCY 10W 830 BK IP65-EN	
	rondor documento	JOI II / IOL DOLIN ILAD /	COO OCTOOTT LIVILITALINOT TOVV OOD DIVII OUTLIN	


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075647428	Folding box	74 mm x 272 mm x 262 mm	932.00 g	5.27 dm ³
4058075647435	Shipping box 8	550 mm x 285 mm x 315 mm	8038.00 g	49.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION









References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.