

# PRODUCT DATASHEET

## PANEL LED 600.00 mm x 300.00 mm 17 W 6500 K

LEDVANCE PANEL LED | LED panel luminaires



### Areas of application

- Offices
- Retail
- Hospitals
- Recreational facilities

### Product benefits

- Low maintenance and operation costs due to long lifetime of LED
- Very slim aluminum housing (only 10.5 mm) and matt white frame
- Edge-lit with LCD backlight technology
- High efficiency and reliability

### Product features

- Available in sizes: 300 x 600 mm, 600 x 600 mm, 300 x 1200 mm and 600 x 1200 mm
- High system efficiency: up to 100 lm/W
- Available with color temperature: 4,000 K, 6,500 K



- Color rendering index  $R_a$ :  $\geq 80$
- Power factor:  $> 0.9$
- Long lifetime: up to 30,000 h
- CCC marked, CB test certificate

## TECHNICAL DATA

### Electrical data

Nominal wattage	17.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor $\lambda$	0.90
Protection class	II

### Photometrical data

Luminous flux	1600 lm
Luminous efficacy	95 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>
Beam angle	120 °

### Dimensions & Weight

Length	600.00 mm
Width	300.00 mm
Height	10.50 mm
Product weight	1500.00 g

### Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-10...+40 °C
Type of connection	Cable/Connector
Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling

Application environment	Indoor
-------------------------	--------

**Lifespan**

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	10000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)


**Certificates & Standards**

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

**EQUIPMENT / ACCESSORIES**

– For recessed mounting (surface or pendant mouting requires mounting accessories)

**DOWNLOAD DATA**

Documents and certificates	Document name
 User instruction / safety instructions	PANEL LED 230VUI

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075003378	Folding box 1	685 mm x 330 mm x 43 mm	1730.00 g	9.72 dm <sup>3</sup>
4058075003385	Shipping box 5	710 mm x 230 mm x 370 mm	9338.00 g	60.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.