

# PRODUCT DATASHEET

## TruSys® PFM VW 35 W/4000 K

TruSys® PERFORMANCE VERY WIDE | Luminaire inserts with very wide light distribution



### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, garages, hardware stores
- Discounters, supermarkets

### Product benefits

- Very wide light distribution for area lighting
- Easy installation, no tools required for connection
- Energy saving and cost-effective
- Flexible application due to a range of different lumen packages and beam angles
- Rows of up to 57 (On-Off) / 66 (DALI) luminaires possible
- Versions with DALI ECG available

### Product features

- Beam angle very wide: 120°
- Click into place solution with smart click buttons
- Luminous efficacy: up to 160 lm/W
- Fixed luminaire taps
- Lumen package 5600 lm, 8000 lm, 11200 lm
- Steel-sheet housing
- Lens material: PMMA



- Type of protection: IP20
- Common family design with LEDVANCE
- Lifetime (L80/B10): up to 60,000 h

## TECHNICAL DATA

### Electrical data


Nominal wattage	35.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	190 mA
Inrush current	25 A
Inrush current time $T_{h50}$	220 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	13
Max. number of luminaires per miniature circuit breaker C10	12
Max. number of luminaires per miniature circuit breaker C16	19
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Integrated LED driver

### Photometrical data


Luminous flux	5600 lm
Luminous efficacy	160 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq$ 80
Standard deviation of color matching	$\leq$ 3 sdc <sub>m</sub>
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG1
Beam angle	120 °
UGR	23



TRUSYS PFM 35W 4000K VW




TRUSYS PFM 35W 4000K VW



TRUSYS PFM 35W 4000K VW

### Dimensions & Weight

Length	1500.00 mm
Width	66.80 mm
Height	39.40 mm
Product weight	1660.00 g



### Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-25...+40 °C
Type of connection	Plug-In connection

Type of protection	IP20
Protection class IK (shock resistance)	IK04
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Mounting rail
Application environment	Indoor
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	65000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	60000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	60000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

Output current	420 mA
ECG - Output ripple current	< 20 %



### Certificates & Standards


Standards	CE / CB / ENEC / EAC
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

### EQUIPMENT / ACCESSORIES









– Mounting rail with fixed integrated 5- and 8-pole cable

### DOWNLOAD DATA



Documents and certificates	Document name
 User instruction / safety instructions	UI_Trusys® TRUNKING SYSTEM PFM ON/OFF
 Legal information	LS Insert Trusys PFM

Documents and certificates		Document name
	Declarations of conformity	CE TRUSYS PFM 35W 4000K VW AC17198


  

Photometric and lighting design files		Document name
	IES file (IES)	TRUSYS PFM 35W 4000K VW
	LDT file (Eulumdat)	TRUSYS PFM 35W 4000K VW
	ULD file (DIALux)	TRUSYS PFM 35W-4000K VW
	ROLF file (RELUX)	TRUSYS PFM 35W-4000K
	UGR file (UGR table)	TRUSYS PFM 35W 4000K VW
	Light distribution curve type cone	TRUSYS PFM 35W 4000K VW
	Light distribution curve type polar	TRUSYS PFM 35W 4000K VW
	Light distribution curve type polar	TRUSYS PFM 35W 4000K VW

CAD/BIM files		Document name
	BIM Revit 3D	TruSys®-Performance
	CAD STEP 3D	TRUSYS PFM INSERT

Tender texts		Document name
	Tender documents	TruSys PERFORMANCE VERY WIDE 35 W4000 K-EN

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075290921	Folding box 1	83 mm x 1,571 mm x 88 mm	1835.00 g	11.47 dm <sup>3</sup>
4058075290938	Shipping box 4	1,589 mm x 194 mm x 198 mm	8133.00 g	61.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.