

# PRODUCT DATASHEET HB 155 W 4000 K 70DEG IP65

HIGH BAY GEN 3 | High-bay luminaires up to 140 lm/W and attractive UGR



# Areas of application

- Replacement for high bay luminaires with mercury vapor or metal halide lamps
- Warehouses
- Logistics halls
- Industry
- High ceiling (e.g. in shopping malls, airports, commercial buildings, lobbies)

#### Product benefits

- Improved UGR compared to previous generations, down to UGR ≤ 22 in combination with reflector
- High luminous efficacy
- Energy savings of up to 60 % compared to conventional high bay luminaires
- 5 years guarantee
- Optimized weight and size due to compact design

#### Product features

 $-\,$  Different luminous flux and beam angle for mounting heights of  $\sim 6$  m to 14 m in 4000 K or 6500 K




# TECHNICAL DATA


# Electrical data

Nominal wattage	155.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	710 mA
Inrush current	49 A
Inrush current time T <sub>h50</sub>	368 µs
Max. number of luminaires per miniature circuit breaker B16	5
Max. number of luminaires per miniature circuit breaker C10	5
Max. number of luminaires per miniature circuit breaker C16	8
Power factor $\lambda$	> 0.95
Total harmonic distortion	≤ 20 %
Protection class	1
Operating mode	Mains voltage

# Photometrical data

Luminous flux	22000 lm
Luminous efficacy	140 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	< 5 sdcm
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	70 °






HB PFM 155W4000K 70DEG IP65

HB PFM 155W4000K 70DEG IP65

# Dimensions & Weight

Diameter	321.00 mm
Height	140.00 mm
Product weight	2300.00 g
Cable length	1500 mm



# Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-30+55 °C
Temperature range at storage	-40+70 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	80000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	50000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	50000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	200000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# Control gear

ECG - Output ripple current	≤ 10 %
= 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	, .

# Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / EAC
Luminaire with limited surface temperature, "D sign"	Yes
Replaceable light source (EPREL)	Not replaceable

# **EQUIPMENT / ACCESSORIES**

- Mounting hook included
- Mounting brackets, reflectors and refractors available as separate accessory

#### DOWNLOAD DATA


	Documents and certificates	Document name	
POF	User instruction / safety instructions	HIGHBAY Gen3	
PDF	Legal information	LSI_HB_LSR label	
PDF	Legal information	Legal insert HB P GEN 4 AND HB GEN 3	
PDF	Declarations of conformity	НВ	
	Photometric and lighting design files	Document name	
	IES file (IES)	HB 155W4000K 70DEG IP65	
	LDT file (Eulumdat)	HB 155W4000K 70DEG IP65	
	UGR file (UGR table)	HB 155W4000K 70DEG IP65	
	Light distribution curve type cone	HB PFM 155W4000K 70DEG IP65	
	Light distribution curve type polar	HB PFM 155W4000K 70DEG IP65	
	CAD/BIM files	Document name	
- I I	BIM Revit 3D	HB GEN3	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075452411	Shipping box	377 mm x 377 mm x 177 mm	2940.00 g	25.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# ADDITIONAL CATALOG INFORMATION



# References / Links

- For Guarantee see www.ledvance.com/guarantee

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.