

# PRODUCT DATASHEET ECO HP FLOOD 300W 840 N 41100LM BK

ECO HIGH POWER FLOODLIGHT | Floodlight with rotational symmetric light distribution for high mast area lighting



#### Areas of application

- Direct replacement for luminaires using HID lamps
- Sports facilities
- Industry
- Lighting of large areas

#### **Product benefits**

- Energy savings of up to 90 % compared to halogen lamp floodlights
- $-\,$  Energy savings of up to 45 % compared to luminaires that use conventional discharge lamps
- Homogeneous light output
- 5 years guarantee

#### **Product features**

- Rotational symmetric light distribution for high mast area lighting
- Various versions with different types of light distribution available
- Mounting bracket for up to 180° tilting
- Pre-installed, flexible 1 m cable (H05RN-F), wrapped 3 x 1.0 mm² single wires



## TECHNICAL DATA

#### Electrical data

Nominal wattage	300.00 W
Nominal voltage	100240 V
Mains frequency	5060 Hz
Nominal current	1550.000 mA
Inrush current	80 A
Inrush current time T <sub>h50</sub>	500 μs
Max. number of luminaires per miniature circuit breaker B16	2
Max. number of luminaires per miniature circuit breaker C10	2
Max. number of luminaires per miniature circuit breaker C16	3
Power factor $\lambda$	> 0.95
Total harmonic distortion	< 20 %
Protection class	1
Operating mode	Mains voltage


## Photometrical data

Luminous flux	41100 lm
Luminous efficacy	137 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	< 5 sdcm
Luminous intensity	-
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	60 °

# ECO CLASS HP FLOODLIGHT NARROW

# Dimensions & Weight

Length	522.00 mm
Width	370.00 mm
Height	152.00 mm
Product weight	10500.00 g
Cable length	1000 mm



HP FLOODLIGHT 300W

## Materials & Colors

Product color	Black
Housing color	Black
RAL Color (most similar)	RAL 9005
Body material	Aluminum
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-40+45 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Outdoor
Adjustable	Yes
With light source	No
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

Standards	CE / EAC / RoHS / REACH
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

|--|

# DOWNLOAD DATA

	Documents and certificates Document name	
PDF	User instruction / safety instructions	UI ECO HP FLOOD 300W BK
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity CE Declaration of Conformity ECO CLASS HP FLOODLIGHT	

Photometric and lighting design files	Document name
LDT file (Eulumdat)	ECOHPFLOOD 300W 840 N41100LM BK
Light distribution curve type polar	ECO CLASS HP FLOODLIGHT NARROW

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075372450	Shipping box	597 mm x 442 mm x 225 mm	11623.00 g	59.37 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For Guarantee see www.ledvance.com/guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.