

# PRODUCT DATASHEET LED PERFORMANCE FL 10W 865

# LED PERFORMANCE FLOODLIGHT | Luminaires



## Areas of application

- Airports
- Area lighting
- Billboard lighting
- Corridors
- Architectural lighting
- Outdoor use (IP65)

## **Product benefits**

- Dust and water protection according to IP65
- Easily installed
- Frosted cover made of tempered glass for uniform illumination
- Designed for extra performance
- Low maintenance costs thanks to long lifetime
- Compact and sleek design

## **Product features**

- Die-cast aluminum housing
- $-\,$  Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Lifetime (L70/B50): 50,000 h



## **TECHNICAL DATA**

## Electrical data

Nominal wattage	10.00 W
Nominal voltage	100277 V
Mains frequency	5060 Hz
Nominal current	49.000 mA <sup>1)</sup>
Power factor $\lambda$	0.90
Total harmonic distortion	20 %
Protection class	I


<sup>1) &</sup>lt;sub>220 V AC</sub>

## Photometrical data

Luminous flux	1200 lm
Luminous efficacy	120 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	< 5 sdcm
Beam angle	100 °

# Dimensions & Weight

Length	131.00 mm
Width	122.00 mm
Height	35.70 mm
Product weight	400.00 g



# Materials & Colors

Product color	Black
---------------	-------

Housing color	Black
Body material	Aluminum
Cover material	Glass
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-30+50 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK07
Dimmable	No
Mounting type	Standing Surface
Mounting location	Ground
Application environment	Outdoor
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
---------------------------	-----------------------

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

	B	eplaceable light source (EPREL)	Not replaceable
--	---	---------------------------------	-----------------

# DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LDPFM FL 10W 865

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075428928	Folding box 1	57 mm x 136 mm x 118 mm	447.00 g	0.91 dm <sup>3</sup>
4058075428935	Shipping box 12	360 mm x 286 mm x 144 mm	5840.00 g	14.83 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.