

PRODUCT DATASHEET ENDURA Style Pyramid Wall 9W

ENDURA STYLE PYRAMID | Stainless steel wall luminaires and bollards with indirect illumination



Areas of application

- Building facades
- Entrance lighting
- Patios, balconies

Product benefits

- Easy and quick installation
- Energy-efficient thanks to LED technology

Product features

- Bright and functional outdoor LED luminaires
- Stainless steel housing
- Type of protection: IP44



TECHNICAL DATA

Electrical data


| Nominal wattage | 9.00 W |
|------------------------|---------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Power factor λ | > 0.5 |
| Protection class | 1 |
| Operating mode | Mains voltage |

Photometrical data

| Luminous flux | 600 lm |
|--------------------------------------|------------|
| Luminous efficacy | 67 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | ≥80 |
| Standard deviation of color matching | < 6 sdcm |
| Beam angle | 90 ° |

Dimensions & Weight

| Length | 125.00 mm |
|----------------|-----------|
| Width | 100.00 mm |
| Height | 100.00 mm |
| Product weight | 650.00 g |



Materials & Colors

| Product color | Steel |
|---------------|-----------------|
| Housing color | Steel |
| Body material | Stainless steel |

| Cover material | Polycarbonate (PC) |
|----------------------------|-----------------------------|
| Application & Mounting | |
| Ambient temperature range | -20+40 °C |
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP44 |
| Dimmable | No |
| Mounting type | Surface |
| Application environment | Outdoor |
| With light source | Yes |
| Replaceable light source | No |
| Lifespan | |
| Lifespan L70/B50 at 25 °C | 25000 h ¹⁾ |
| Number of switching cycles | 12500 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| Standards | CE / UKCA / EAC |
|--|-----------------|
| Luminaire with limited surface temperature, "D sign" | No |
| Replaceable light source (EPREL) | Not replaceable |

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|--|----------------------|
| PDF | User instruction / safety instructions | ENDURA STYLE PYRAMID |

| | Documents and certificates | Document name |
|-----|---------------------------------|--------------------------------------|
| PDF | Legal information | Safety insert G11219578 |
| PDF | Declarations of conformity | ENDURA STYLE PYRAMID WALL 9W ST LEDV |
| PDF | Declarations of conformity UKCA | Fixed LUM |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854461781 | Folding box 1 | 107 mm x 107 mm x 139 mm | 780.00 g | 1.59 dm ³ |
| 4099854461798 | Shipping box 4 | 228 mm x 228 mm x 164 mm | 3118.00 g | 8.53 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.