

PRODUCT DATASHEET

ENDURA Classic Calice Wall Sensor E27

ENDURA CLASSIC CALICE | Stainless steel luminaires with glass diffuser



Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

Product benefits

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

Product features

- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



TECHNICAL DATA

Electrical data


| | |
|------------------------|---------------|
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Power factor λ | > 0.50 |
| Protection class | I |
| Operating mode | Mains voltage |

Photometrical data

| | |
|--------------------------------------|----------------------|
| Standard deviation of color matching | < 6 sdc _m |
|--------------------------------------|----------------------|

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 161.00 mm |
| Width | 120.00 mm |
| Height | 305.00 mm |
| Product weight | 950.00 g |



ENDURA CLASSIC CALICE WALL
S E27 SI

Materials & Colors

| | |
|-----------------|-----------------|
| Product color | Steel |
| Housing color | Steel |
| Body material | Stainless steel |
| Cover material | Glass |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

| | |
|--------------------------|-----------------------------|
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP44 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Wall |
| Application environment | Outdoor |
| With light source | No |
| Replaceable light source | No |

Sensor

| | |
|--|------------------------|
| Type of sensor | Light / Motion |
| Sensor technology | Passive infrared (PIR) |
| Sensor detection angle | 90 ° |
| Sensor controlled switching time | 5 s...6 min |
| Detection range of motion sensor | 5...8 m |
| Detection threshold of daylight sensor | 0...30 lx |

Certificates & Standards

| | |
|--|-----------------|
| Standards | CE / EAC / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |

Additional product data

| | |
|----------------|----------------------------|
| Product remark | Maximum bulb wattage: 60 W |
|----------------|----------------------------|





EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|---|--|------------------------------|
|  | User instruction / safety instructions | ENDURA CLASSIC CALICE |
|  | Legal information | Legal insert I-Outdoor |
|  | Declarations of conformity | ENDURA CLASSIC CALICE WALL S |
|  | Declarations of conformity UKCA | CLASSIC CALICE WALL |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075477971 | Folding box 1 | 202 mm x 162 mm x 349 mm | 1109.00 g | 11.42 dm³ |
| 4058075477988 | Shipping box 4 | 420 mm x 365 mm x 340 mm | 5230.00 g | 52.12 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.