

PRODUCT DATASHEET

LINK CONTROLLER 3.5mm AUX12V BLE

Networked Lighting Controls | Networked Lighting Controls



TECHNICAL DATA

Electrical data

Nominal wattage	0.45 W
Nominal voltage	12 V
Mains frequency	35 Hz
Protection class	N

Dimensions & Weight

Length	66.29 mm
Width	66.29 mm
Height	59.94 mm
Product weight	26.3 g

Materials & Colors

Mercury content	0.0 mg
-----------------	--------







Application & Mounting



Type of protection	IP66
Dimmable	Yes
Type of dimming	0-10V

Additional product data

NAED	62630
------	-------

DOWNLOAD DATA

	Spec Sheets and Product Documents	Document name
	Extended installation guide	INSTALLATION GUIDE 3.5mm PIN BLUETOOTH® LOW ENERGY MESH INDOOR CONTROLLER
	Extended installation guide	INSTALLATION GUIDE LEDVANCE LINK SENSOR ADAPTER
	Extended installation guide	INSTALLATION GUIDE L-SHAPE SIDE ADAPTER
	Extended installation guide	INSTALLATION GUIDE SENSOR SOCKET ADAPTER
	Extended installation guide	USER GUIDE LEDVANCE LINK FW Manager
	Product information bulletin	DATASHEET 3.5mm PIN BLUETOOTH MESH LOW VOLTAGE CONTROLLER

Spec Sheets and Product Documents		Document name
	Product information bulletin	SubstiKIT LED T5 & T8 Type C System
	Product information bulletin	LEDLUM189 Wattage Selectable Area Flood 5A

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135626302	Folding box 1	70 mm x 70 mm x 65 mm	39.00 g	0.32 dm³
4058075777118	Shipping box 100	370 mm x 370 mm x 280 mm	4305.00 g	38.33 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.