

PRODUCT DATASHEET

CYLINDER OPTI-SELECT S020 UNH D 8 SC2 R4 WH P

CYLINDER OPTI-SELECT | Cylinder luminaire with field adjustable beam angles and up/down light



Areas of application

- Building facades
- Entryways
- Wall washing

Product features

- OPTI-SELECT: narrow, medium and wide beam angles, adjustable via switch
- Up, down, or up + down light modes
- Up to 125 LPW
- Selectable CCTs: 3000/4000/5000K
- CRI > 80
- Selectable wattage and lumen outputs
- Integrated photocell that can be disabled in the field

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Nominal voltage	120...347 V

Photometrical data

Luminous flux	1100 ... 2200 lm
Luminous efficacy	110 lm/W
Color temperature	3000 ... 5000 K
Color rendering index Ra	80

Dimensions & Weight

Diameter	101.60 mm
Product weight	2050.00 g




Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Surface
Application environment	Outdoor
Replaceable light source	No

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	OPTISELECT CYLINDER INSTALL MANUAL
	Product information bulletin	LEDLUM224 LEDVANCE LUMINAIRES OPTI-SELECT CYLINDER
Photometric and lighting design files		Document name
	IES file (IES)	CYLINDER OPTISELECT IES SPD

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135662898	Folding box 1	185 mm x 141 mm x 299 mm	3658.00 g	7.80 dm ³
4099854401688	Shipping box 6	443 mm x 390 mm x 320 mm	14651.00 g	55.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.