

PRODUCT DATASHEET REMOTE LED 2I WH

EMERGENCY LIGHTS SELF DIAGNOSTIC | LEDVANCE LED Emergency Lights with self diagnostic and remote capable options





Product features

- Slim profile, lightweight, easy to install emergency light that replaces traditional incandescent and fluorescent emergency lights
- Bright, energy-efficient LEDs provide energy savings up to 97%
- Offered in watts up to 2W
- Surface mounting
- 6500K color temperature
- CRI > 80
- Optional self-diagnostic and remote capable

TECHNICAL DATA

Electrical data

Nominal wattage	2.40 W
Nominal voltage	3,6 V

Photometrical data

Luminous flux	200 lm
Luminous efficacy	83 lm/W
Color temperature	6500 K
Color rendering index Ra	80

Dimensions & Weight

Length	214.00 mm
Width	108.00 mm
Height	75.70 mm
Product weight	350.00 g

Materials & Colors

Product color	White
Housing color	White
Mercury content	0.0 mg

Application & Mounting

Dimmable	No
Mounting type	Surface
Replaceable light source	No

Certificates & Standards

Additional product data

NAED 66077

DOWNLOAD DATA

	Spec Sheets and Product Documents	Document name
POF	Extended installation guide	EXIT & EMERGENCY LIGHT
PDF	Product information bulletin	LEDLUM231 LEDVANCE LUMINAIRES EXIT AND EMERGENCY LIGHTING

Photometric and lighting design files	Document name	
IES file (IES)	VALUE CLASS EXIT AND EMERGENCY	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135660771	Folding box 1	116 mm x 86 mm x 232 mm	448.00 g	2.31 dm ³
4099854335105	Shipping box 12	480 mm x 275 mm x 245 mm	5645.00 g	32.34 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.