

PRODUCT DATASHEET

PUFF CEILING CCT SELECT 120-277V

SENSOR

SYLVANIA Puff Ceiling CCT Selectable | SYLVANIA Puff Ceiling luminaire with selectable CCT



Areas of application

- Indoor applications
- Home offices & study rooms
- Bedrooms & living rooms
- Entryways & foyers
- Nurseries & children's rooms

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- Dimmable
- Sensor and integrated emergency battery backup available
- Easy installation – no additional hardware needed
- Lifetime (L70): up to 50,000 h
- No warm up time, instant on with full light and consistent lamp to lamp color

TECHNICAL DATA

Electrical data

Nominal wattage	21.00 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	1500 lm
Luminous efficacy	71 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	381.00 mm
Height	71.88 mm
Product weight	656.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Surface
Application environment	Indoor
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	62042
------	-------

EQUIPMENT / ACCESSORIES

- Mounting screws and mounting brackets included

Safety advice

- cETLus, RoHS, ENERGY STAR
- For indoor use only; not suitable for outdoor or wet locations
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product information bulletin	Hi-PerformanceLED Puff Ceiling
Photometric and lighting design files		Document name
	IES files (IES, additional)	Flush Mount LM79s Zip
	IES files (IES, additional)	Performance Class Puff Series .ies

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135620423	Folding box 1	91 mm x 398 mm x 399 mm	913.00 g	14.45 dm ³
4058118200306	Shipping box 4	419 mm x 387 mm x 424 mm	4685.00 g	68.75 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.