

PRODUCT DATASHEET

LINK SENSOR PIR 40FT 3.5mm BLE WH

LEDVANCE LINK™ PLUG AND PLAY MOTION SENSOR | LEDVANCE LINK Plug and Play Motion Sensors



Product features

- Commission and configure with LEDVANCE LINK™ app
- Control using either the LEDVANCE LINK™ app or the wireless controller
- Grouping and Zoning: Wirelessly group luminaires to act in sync with each other
- Scene Control: Preset various scenes for individual or group of luminaires using the app and/or wireless/wired controllers
- QR Code for Admin/Guest control: Using the LEDVANCE LINK™ app, Admin and Guest QR codes for each zone can be generated. Allows copying the settings to another phone/tablet by scanning this QR code
- Allows setting time-based schedules and high-end and low-end trim through the LEDVANCE LINK™ app

TECHNICAL DATA

Electrical data

Nominal wattage	0.45 W
Nominal voltage	12 V
Mains frequency	35 Hz

Dimensions & Weight

Length	59.94 mm
Width	66.29 mm
Height	59.94 mm
Product weight	48.00 g









Capabilities




Dimmable	Yes
----------	-----

Certificates & Standards

Protection class	N
Type of protection	IP66

DOWNLOAD DATA

	Documents and certificates	Document name
	Extended installation guide	INSTALLATION GUIDE LEDVANCE LINK SENSOR ADAPTER
	Extended installation guide	INSTALLATION GUIDE L-SHAPE SIDE ADAPTER
	Extended installation guide	INSTALLATION GUIDE SENSOR SOCKET ADAPTER
	Extended installation guide	INSTALLATION GUIDE LEDVANCE LINK 3.5mm PIN BLUETOOTH® LOW ENERGY MESH INDOOR SENSOR & CONTROLLER
	Extended installation guide	USER GUIDE LEDVANCE LINK FW Manager
	Product information bulletin	DATASHEET LEDVANCE LINK 3.5mm PIN BLUETOOTH® LOW ENERGY MESH INDOOR SENSOR & CONTROLLER
	Product information bulletin	SubstiKIT LED T5 & T8 Type C System
	Product information bulletin	ULTRA LED™ Selectable HIDR

	Documents and certificates	Document name
	Product information bulletin	ULTRA LED™ CCT Selectable High Bay Retrofit
	Product information bulletin	LEDLUM189 Wattage Selectable Area Flood 5A
	Product information bulletin	UltraLED™ Dual Selectable Vapor Tight 3A

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135626340	Folding box 1	70 mm x 70 mm x 65 mm	60.00 g	0.32 dm³
4058075777170	Shipping box 100	370 mm x 370 mm x 280 mm	6475.00 g	38.33 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.