

PRODUCT DATASHEET

DOOR KIT LINK 2x2 UNV

DOOR KIT LINK™ | Door Kit luminaire featuring built-in LEDVANCE LINK bluetooth low energy mesh connectivity



Areas of application

- Offices
- Retail
- Hallways
- Multipurpose Rooms
- Hospitality

Product features

- Selectable CCT: 3000/3500/4000/5000K
- Bluetooth® Low Energy Mesh and a range of up to 100 ft between luminaires
- Easy to deploy - install, commission, and control
- Convenient control via LINK™ app or wireless wall/controller
- Optional LINK PIR sensor enables field-installable occupancy & daylight control
- DLC listing maximizes rebate opportunities
- Up to 125 LPW
- Optional emergency battery backup versions
- CRI > 80
- Wirelessly sync luminaires and set group/individual scenes using the LINK app

TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	1905 ... 3810 lm
Luminous efficacy	125 lm/W
Color temperature	3000 ... 5000 K
Color rendering index Ra	> 80

Dimensions & Weight

Length	605.00 mm
Width	606.00 mm
Height	78.50 mm
Product weight	3930.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	0-10V
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No


Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	62572
------	-------

Accessories Optional

Product image	Product name	EAN
	AREA DUSK-TO-DAWN 55W 120-277V D 3CCT T5 GR P	10046135617512






EQUIPMENT / ACCESSORIES

- Mounting brackets

Safety advice

- Retrofit luminaire is designed to be installed in existing troffers

DOWNLOAD DATA

	Spec Sheets and Product Documents	Document name
	Extended installation guide	RETROFIT DOOR KIT 7A
	Extended installation guide	INSTALLATION GUIDE LEDVANCE LINK LOW-VOLTAGE PLUG&PLAY ECOSENSOR
	Product information bulletin	BLUETOOTH MESH ENABLED CONNECTED RETROFIT DOOR KIT LEDLUM165
	Photometric and lighting design files	Document name
	IES file (IES)	VOLUME DOORKIT 7A IES
	IES files (IES, additional)	LEDVANCE Link .ies + LM79s

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075774063	Shipping box 2	676 mm x 639 mm x 136 mm	8838.00 g	58.74 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.