



# PRODUCT DATASHEET

## DOOR KIT LINK 1x4 EMBB UNH

DOOR KIT LINK™ | Door Kit luminaire featuring built-in LEDVANCE LINK bluetooth low energy mesh connectivity

---

### Areas of application

- Offices
- Retail
- Hallways
- Multipurpose Rooms
- Hospitality

---

### Product features

- Selectable CCT: 3000/3500/4000/5000K
- Bluetooth® Low Energy Mesh and a range of up to 100 ft between luminaires
- Easy to deploy - install, commission, and control
- Convenient control via LINK™ app or wireless wall/controller
- Optional LINK PIR sensor enables field-installable occupancy & daylight control
- DLC listing maximizes rebate opportunities
- Up to 125 LPW
- Optional emergency battery backup versions
- CRI > 80
- Wirelessly sync luminaires and set group/individual scenes using the LINK app

## TECHNICAL DATA

### Electrical data

|                 |             |
|-----------------|-------------|
| Nominal wattage | 30.00 W     |
| Nominal voltage | 120...347 V |

### Photometrical data

|                          |                  |
|--------------------------|------------------|
| Luminous flux            | 1905 ... 3810 lm |
| Luminous efficacy        | 127 lm/W         |
| Color temperature        | 3000 ... 5000 K  |
| Color rendering index Ra | > 80             |

### Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 1215.00 mm |
| Width          | 302.00 mm  |
| Height         | 78.50 mm   |
| Product weight | 4050.00 g  |

### Materials & Colors

|                 |        |
|-----------------|--------|
| Product color   | White  |
| Housing color   | White  |
| Body material   | Steel  |
| Mercury content | 0.0 mg |

### Application & Mounting

|                          |          |
|--------------------------|----------|
| Dimmable                 | Yes      |
| Type of dimming          | 0-10V    |
| Mounting type            | Recessed |
| Application environment  | Indoor   |
| Replaceable light source | No       |

### BATTERY

|                    |        |
|--------------------|--------|
| Battery size [GMS] | Others |
|--------------------|--------|

### Certificates & Standards

|                                  |                 |
|----------------------------------|-----------------|
| Replaceable light source (EPREL) | Not replaceable |
|----------------------------------|-----------------|

### Additional product data

|      |       |
|------|-------|
| NAED | 64284 |
|------|-------|

### Accessories Optional

| Product image                                                                     | Product name                                  | EAN            |
|-----------------------------------------------------------------------------------|-----------------------------------------------|----------------|
|  | AREA DUSK-TO-DAWN 55W 120-277V D 3CCT T5 GR P | 10046135617512 |

## EQUIPMENT / ACCESSORIES

- Mounting brackets

## Safety advice

- Retrofit luminaire is designed to be installed in existing troffers

## DOWNLOAD DATA

| Spec Sheets and Product Documents                                                  |                              | Document name                                                 |
|------------------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------|
|    | Product information bulletin | BLUETOOTH MESH ENABLED CONNECTED RETROFIT DOOR KIT LEDLUM165  |
| Photometric and lighting design files                                              |                              | Document name                                                 |
|  | IES file (IES)               | IES files for DUAL SELECTABLE RETROFIT DOOR KIT GENERATION 7B |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854609053 | Unpacked<br>2                |                                      |              |                       |
| 4099854311109 | Shipping box<br>2            | 1,241 mm x 322 mm x 130 mm           | 9007.00 g    | 51.95 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.