



PRODUCT DATASHEET

LEDMD BLAZEGUARD 4" 5CCT 800LM 120V

MICRODISK SLIM BLAZE GUARD™ FLAME RESISTANT | Slim Microdisk Downlight with Blaze Guard flame resistant technology and selectable 5 CCT

Areas of application

- Residential
- Commercial applications
- Fire resistant ceilings
- Multi-family housing
- Shipbuilding applications

Product features

- Canless recessed flush mount downlight with remote driver design for easy installation
- Tested to UL263 for flame resistance of 1100 °C for up to 2 hours
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Up to 86 LPW
- Energy savings up to 92 %
- 1/2" height allows installation directly under joists
- Beam Angle of 110° FWHM
- 90 CRI, R9>50

TECHNICAL DATA

Electrical data

Nominal wattage	10.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	800 lm
Luminous efficacy	80 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	175.00 mm
Height	23.50 mm
Product weight	264.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	63426
------	-------

Accessories Optional

Product image	Product name	EAN
	SLIM MD FRAME	0046135629594

Product image	Product name	EAN
	MD FRAME T-GRID	0046135637438

EQUIPMENT / ACCESSORIES

- Luminaire with interconnected cable to galvanized steel remote driver wiring enclosure via FT6 cable
- Quick Connectors

Safety advice

- Suitable for indoor, dry, and wet locations.
- Not intended for use with emergency light luminaires or exit lights.
- Suitable for use in closets, compliant with NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5).
- IC Rated.
- Air Tight certified in accordance with ASTM E283-2004.
- Max Ceiling Thickness 1.18" (30 mm).

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Extended installation guide	FLAME RESISTANT SELECTABLE SLIM MICRODISK MANUAL
	Product information bulletin	FLAME RESISTANT SELECTABLE SLIM MICRODISK
Photometric and lighting design files		Document name
	IES file (IES)	FLAME RESISTANT SELECTABLE SLIM MICRODISK IES

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135634260	Folding box 1	149 mm x 69 mm x 140 mm	326.00 g	1.44 dm ³
10046135634267	Shipping box 6	308 mm x 218 mm x 154 mm	2146.00 g	10.34 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

