



PRODUCT DATASHEET

LEDMD SLIM SELECT 3A 4" 5CCT 800LM

UNV WH

MICRODISK SLIM PERFORMANCE CCT SELECTABLE | Slim Microdisk Downlight with selectable 5 CCT

Areas of application

- Residential
- Commercial applications
- New installations or retrofit of existing installations
- Closets
- Cabinet lighting

Product features

- Canless recessed flush mount downlight with remote driver design for easy installation
- 1/2" height allows installation directly under joists
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Flicker-free dimming
- Up to 87 LPW
- Energy savings up to 92 %
- Beam Angle of 110° FWHM
- 90 CRI, R9>50

TECHNICAL DATA

Electrical data

Nominal wattage	13.00 W
Nominal voltage	120...277 V

Photometrical data

Luminous flux	800 lm
Luminous efficacy	61 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	125.00 mm
Height	22.86 mm
Product weight	263.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Mercury content	0.0 mg

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Application environment	Indoor
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	63598
------	-------

Accessories Optional

Product image	Product name	EAN
	MD EXT CABLE 6FT WH	0046135608988
	MD EXT CABLE 10FT WH	0046135608995

Product image	Product name	EAN
	MD EXT CABLE 20FT WH	0046135609008
	SLIM MD FRAME	0046135629594
	MD FRAME T-GRID	0046135637438
	SLIM MD TRIM 3A 12" SATIN NCKL	0046135632167
	SLIM MD TRIM 3A 3" BL	0046135632020
	SLIM MD TRIM 3A 3" BZ	0046135632037
	SLIM MD TRIM 3A 3" SATIN NCKL	0046135632044
	SLIM MD TRIM 3A 4" BL	0046135632051
	SLIM MD TRIM 3A 4" BZ	0046135632068
	SLIM MD TRIM 3A 4" SATIN NCKL	0046135632075
	SLIM MD TRIM 3A 6" BL	0046135632082
	SLIM MD TRIM 3A 6" BZ	0046135632099
	SLIM MD TRIM 3A 6" SATIN NCKL	0046135632105
	SLIM MD TRIM 3A 8" BL	0046135632112
	SLIM MD TRIM 3A 8" BZ	0046135632129
	SLIM MD TRIM 3A 12" BL	0046135632143
	SLIM MD TRIM 3A 12" BZ	0046135632150
	SLIM MD TRIM 3A 8" SATIN NCKL	0046135632136

EQUIPMENT / ACCESSORIES

- Luminaire with interconnected cable to galvanized steel remote driver wiring enclosure via 16in (400mm) FT6 cable

Safety advice

- Suitable for wet locations.
- Suitable for use in closets, compliant with NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5).

- IC Rated.
- Max Ceiling Thickness 1.18" (30 mm).

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product information bulletin	SLIM CCT SELECTABLE MICRODISK LEDLUM178
Photometric and lighting design files		Document name
	IES file (IES)	SLIM CCT SELECTABLE MICRODISK IES FILES

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135635984	Folding box 1	69 mm x 134 mm x 130 mm	332.00 g	1.21 dm ³
4099854133350	Shipping box 6	289 mm x 255 mm x 168 mm	2140.00 g	12.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.