

PRODUCT DATASHEET

EV COMMERCIAL GEN 1 48 AMPS 4G

PHASE EV™ EV Charger Commercial Generation 1 | LEDVANCE Commercial Level 2 EV Charger Generation 1



Areas of application

- Office parks
- Retail
- Education
- Hospitality

Product features




- 48 Amps, 208/240V
- 4.3" LCD display with charging status light bar
- Rugged NEMA 4 and IP66 hardware enclosure
- 25 ft charge cable with SAE J1772 Type 1 connector
- Built-in WiFi and Ethernet Connectivity
- Standard 4G module with Super SIM
- Configurable for free plug & charge operation
- Pre-configured for use with an optional subscription to AmpUp CPO software
- OCPP Compliant
- -22°F to +122°F

TECHNICAL DATA

Dimensions & Weight

Product weight	14000.00 g
----------------	------------

Accessories Optional

Product image	Product name	EAN
	EV PEDESTAL COMMERCIAL GEN 1 BASE PEDESTAL	10046135781350
	EV PEDESTAL COMMERCIAL GEN 1 SIDE BY SIDE MOUNTING PLATE	10046135781374
	EV PEDESTAL COMMERCIAL GEN 1 PEDESTAL EXTENDER WITH CABLE MANAGEMENT	10046135781367


EQUIPMENT / ACCESSORIES

- Wall mounting hardware

Safety advice

- cETLus
- FCC Part 15 Class B; CAN ICES-003(B)/NMB-003(B)
- UL2594 compliant
- UL991, UL1998, UL2231
- ENERGY STAR

DOWNLOAD DATA

Documents and certificates	Document name
 Product information bulletin	EV001 PHASE EV COMMERCIAL CHARGING STATION

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854098352	Shipping box 1	545 mm x 383 mm x 303 mm	16500.00 g	63.25 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.