

PRODUCT DATASHEET

EV RESIDENTIAL 48 AMPS

PHASE EV™ EV Charger Residential | LEDVANCE Residential Level 2 EV Charger



Areas of application

- Single family residential
- Multi-family residential
- EV dealerships
- EV repair stations
- Indoor and outdoor

Product features

- 11.5 kW max. output power @240 VAC
- Hardwired with a 28" input cable for a secure, reliable connection
- SAE J1772 connector
- 48A max. current can be adjusted to meet the requirements of the installation
- Plug & Play or controlled using smart app
- 25 ft charging cable
- Built-in WiFi / Bluetooth® Connectivity
- IP65 for indoor or outdoor use
- IK10 impact protection
- Dynamic LED status light
- Charging handle cradle with integrated cable management

TECHNICAL DATA

Electrical data

Nominal wattage	11500.00 W
Nominal voltage	208...240 V
Mains frequency	60 Hz

Dimensions & Weight

Length	211.00 mm
Width	191.00 mm
Height	84.60 mm
Product weight	8165.00 g

Capabilities

Dimmable	No
----------	----

EQUIPMENT / ACCESSORIES

- Wall mounting hardware

Safety advice

- cETLus
- FCC
- UL2594 compliant
- NEC625 compliant
- Requires hardwiring to a UL approved junction box.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	Residential EV Charger Installation Instructions

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854293092	Folding box 1			
4099854231063	Shipping box 2	464 mm x 413 mm x 430 mm	19709.00 g	82.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.