

PRODUCT DATASHEET Contractor Series Reflectors R20 5W DIM 10YR 3000K 2PK

SYLVANIA Contactor Series Reflectors | Entry Level LED Reflectors



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- 11,000 hours lifetime (L70)
- CRI of 80 ensures good color definition
- No warm-up time, instant-on with full light output and stable color
- $-\,$ Dimmable down to 10 %

TECHNICAL DATA

Electrical data

Nominal wattage	5 W
Construction wattage	5.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	50 W

Photometrical data

Luminous flux	325 lm
Luminous efficacy	65 lm/W
Color temperature	3000 K
Color rendering index Ra	80
Light color	830

Dimensions & Weight

Overall length	95.00 mm
Diameter	64.01 mm
Product weight	53.00 g

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
NAED	40339

Capabilities

Country-specific categorizations

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	95.00 mm
Height	64.01 mm
Width	64.01 mm

Safety advice

- -4°F to +104°F (-20°C to +40°C)
- Not for use with emergency light fixtures or exit lights.
- Not for use in totally enclosed fixtures.

DOWNLOAD DATA

	Spec Sheets and Product Documents Document name	
PDF	Product information bulletin	Contractor Series LED Reflector Lamps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135403392	Folding box 2	70 mm x 117 mm x 102 mm	142.00 g	0.83 dm ³
10046135403399	Shipping box 12	243 mm x 224 mm x 121 mm	1053.00 g	6.56 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.