

PRODUCT DATASHEET

ULTRA LED™ Glass PAR Lamps 11W

PAR30LN DIM 5000K FL 40 1PK

SYLVANIA ULTRA LED™ PAR Lamps | ULTRA LED PAR Lamps



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Longer life than traditional halogen lamps
- Glass body with full optics – similar to halogen PAR lamps
- CRI of 80 ensures good color definition
- RoHS compliant, mercury and lead free
- Dimmable down to 10 %
- Wet rated



TECHNICAL DATA

Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	75 W

Photometrical data

Luminous flux	850 lm
Luminous efficacy	77 lm/W
Color temperature	5000 K
Color rendering index Ra	82
Light color	850

Dimensions & Weight

Overall length	116.99 mm
Diameter	95.00 mm
Product weight	220.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
NAED	74603

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Type of protection	IP66
--------------------	------

Standards	RoHS / CSA / FTC / FCC / cULus
-----------	--------------------------------

Country-specific categorizations

Order reference	SILV 11W/850 12
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	116.99 mm
Height	95.00 mm
Width	95.00 mm

Safety advice

- Suitable for wet locations.
- -4°F to +113°F (-20°C to +45°C)
- Not for use with emergency light fixtures or exit lights.
- Approved for use in enclosed fixtures.

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product information bulletin	ULTRA LED Glass PAR Lamps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135746031	Folding box 1	102 mm x 114 mm x 171 mm	324.00 g	1.99 dm ³
10046135746038	Shipping box 6	330 mm x 257 mm x 181 mm	2245.00 g	15.37 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.