

PRODUCT DATASHEET

F T5 4W CW BL 16

SYLVANIA Preheat T5 | Miniature preheat T5 lamps for magnetic ballast systems with starter use



Product features

- 6 inch lamps available in Cool White phosphor
- 9 inch lamps available in Cool White phosphor
- 12 inch lamps available in Soft (Warm) White and Cool White phosphor
- 21 inch lamps available in Soft (Warm) White and Cool White phosphor



TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	135 lm
Luminous efficacy	33 lm/W
Color temperature	4200 K
Color rendering index Ra	62
Light color	642
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	150.09 mm
Diameter	16.00 mm
Tube diameter	16 mm
Product weight	15.00 g

Lifespan

Service life	4500 h
--------------	--------

Additional product data

Base (standard designation)	G5
Mercury content	5.0 mg
Design / version	Basic T5 short tubular, G5 base
NAED	20415

Country-specific categorizations

Order reference	F4T5CWBL16 6/CS
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G5
Length	152.40 mm
Height	16.00 mm

Width	16.00 mm
-------	----------

Safety advice

- Starter required for operation.
- Operate on magnetic ballasts.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135204159	Blister 1	219 mm x 73 mm x 18 mm	22.00 g	0.29 dm ³
10046135204156	Shipping box 6	114 mm x 58 mm x 233 mm	200.00 g	1.54 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.