

PRODUCT DATASHEET

LEDVANCE HE BALLAST 4X54W T5 HO UNV PS N HT SCL DOE

T5 FLUORESCENT BALLASTS 120-277V | T5/T5HO programmed rapid start ballasts with low THD and universal 120-277V input



Product features

- High-efficiency operation with energy savings and long system life
- Universal 120–277V input for flexible applications
- Low THD and high power factor
- Compatible with ANSI-standard fluorescent lamp equivalents
- Backed by a five-year limited warranty

TECHNICAL DATA

Electrical data

Nominal wattage	54.00 W
Nominal voltage	120...277 V
Mains frequency	50...60 Hz

Dimensions & Weight

Length	425.45 mm
Width	45.72 mm
Height	30.48 mm
Product weight	1360.00 g

Additional product data

NAED	75872
------	-------



Capabilities

Dimmable	No
----------	----

Certificates & Standards

Protection class	1
------------------	---

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Certificates	LEDVANCE Ballast Limited Warranty
	Product information bulletin	LEDVANCE T5HO & T5 Programmed Rapid Start ECS310

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135758720	Unpacked 1	425 mm x 46 mm x 30 mm	1360.00 g	0.59 dm ³
4099854028489	Shipping box 4	445 mm x 144 mm x 70 mm	5640.00 g	4.48 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.